

AMENDMENTS TO THE CLAIMS

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (**Currently amended**) A coin mechanism for a vending machine requiring at least one coin before a selected product will be dispensed, comprising:

a support member having an inner surface and an outer surface;

a channel member movably connected to the support member, the channel member having a contoured channel formed thereon, the channel configured to define a coin slot when the channel member is in contact with the support member, the channel configured to receive and guide the at least one coin to a desired location, an actuator opening formed on the support and channel members at a location corresponding to the location of the at least one coin in the desired location, the channel member configured to normally be in contact with the support member and to displace relative to the support member when the coin mechanism is actuated;

a coin return actuator connected to the support member, the return actuator comprising at least one protrusion protruding through the support member, the protrusion configured to hold the at least one coin at least in part against a wall of the contoured channel when the channel member is in contact with the support member, the protrusion further configured to travel in a second actuator opening formed on the support member to release the at least one coin into a coin return receptacle upon actuation of the coin return actuator;

an actuator configured to be actuated by a user, comprising

a contact portion disposed frontward of the support member,

at least one support element movably disposed through the support and channel members, the at least one support element having a front portion disposed between the contact portion and the support member, and

an actuation member configured to protrude through the actuator opening in the support member and engage transmit an actuation force from the user onto the coin to press the at least one coin disposed in the desired location against the channel member upon actuation of the coin mechanism to pivotally displace the channel member relative to the support member; and

a product support member connected to the channel member, the product support member comprising an edge configured to releasably support the selected product disposed in a product receptacle, the edge configured to not support the selected product upon actuation of the coin mechanism, causing the selected product to be dispensed, the product support member further configured to releasably engage at least one product in the product receptacle disposed above the selected product following the dispensation of the selected product.

7. (Original) The coin mechanism of Claim 6, wherein the channel member is hinged to the support member.

8. (Original) The coin mechanism of Claim 6, wherein the channel member is rotatably connected to the support member.

9. (Original) The coin mechanism of Claim 6 further comprising at least one coin guide attached to the channel member and protruding over the contoured channel, wherein the at least one coin guide is configured to prevent the at least one coin disposed in the contoured channel from being released to the coin return receptacle when the channel member is displaced relative to the support member during actuation of the coin mechanism.

10. (Original) The coin mechanism of Claim 6, wherein the channel member is configured to release at least one coin into a coin bank when the channel member is displaced relative to the support member during actuation of the coin mechanism.

11. (Original) The coin mechanism of Claim 6, wherein the actuation member is configured to protrude through the actuator opening formed on the channel member when the actuator is actuated by a user without the at least one coin disposed in the desired location, preventing the selected product from being dispensed.

12. (Original) The coin mechanism of Claim 6, wherein a spring is disposed between the channel member and the product receptacle, the spring configured to displace a flag member

to engage at least one product disposed above the selected product through an opening in the product receptacle during actuation of the coin mechanism.

13. (Original) The coin mechanism of Claim 12, wherein a second spring is disposed at the front portion of the at least one support element, the second spring configured to generate a return force on the contact portion when the actuator is actuated by a user.

14. (Original) The coin mechanism of Claim 6, wherein the product support member is removably attached to the channel member.

15. (Original) The coin mechanism of Claim 6, wherein the product support member defines an opening, the support member displaced upon actuation of the coin mechanism so that the edge removes support from the selected product, causing the selected product to be dispensed through the opening.

16. (Canceled).

17. (Canceled).

18. (Canceled).

19. (**Currently amended**) A coin mechanism for a vending machine requiring at least one coin before a selected product will be dispensed, comprising:

a support member having an inner surface and an outer surface;

a channel member rotatably connected to the support member, the channel member having a contoured channel formed thereon, the channel configured to define a coin slot when the channel member is in contact with the support member, the coin slot configured to receive and guide the at least one coin to a desired location, an actuator opening formed on the support and channel members at a location corresponding to the location of the at least one coin in the desired location, the channel member configured to normally be in contact with the support member and to displace relative to the support member when the coin mechanism is actuated, releasing at least one coin disposed in the contoured channel into a coin bank;

a coin guide attached to the channel member and protruding over the contoured channel, wherein the coin guide is configured to prevent the at least one coin disposed in the contoured channel from being released to a coin return receptacle when the channel

member is displaced relative to the support member during actuation of the coin mechanism;

a coin return actuator connected to the support member, the return actuator comprising at least one protrusion protruding through the support member, the protrusion configured to hold the at least one coin at least in part against a wall of the contoured channel of the channel member when the channel member is in contact with the support member, the at least one protrusion further configured to travel in a second actuator opening formed on the support member to release the at least one coin into the coin return receptacle upon actuation of the coin return actuator;

an actuator configured to be actuated by a user, comprising

a contact portion disposed frontward of the support member,

at least one support element movably disposed through the support and channel members, the at least one support element having a front portion disposed between the contact portion and the support member,

an actuation member configured to protrude through the actuator opening in the support member and engage transmit an actuation force from the user onto the coin to press the at least one coin disposed in the desired location against the channel member upon actuation of the coin mechanism to pivotally displace the channel member relative to the support member, the actuation member further configured to protrude through the actuator opening formed on the channel member when the actuator is depressed by the user without the at least one coin disposed in the desired location, preventing the selected product from being dispensed,

a spring disposed between the channel member and a product receptacle, the spring configured to displace a flag member to engage at least one product disposed above the selected product through an opening in the product receptacle during actuation of the coin mechanism, and

a second spring disposed at the front portion of the at least one support element, the second spring configured to generate a return force on the contact portion when the actuator is actuated by the user; and

a product support member removably attached to the channel member, the product support member comprising an edge configured to releasably support the selected product disposed in the product receptacle, the product support member further defining an opening, the support member displaced upon actuation of the coin mechanism so that the edge disengages the selected product, allowing the selected product to be dispensed through the opening, the support member further configured to releasably support at least one product in the product receptacle disposed above the selected product upon dispensation of the selected product.

20. (Canceled).

21. (Canceled).

22. (Canceled).

23. (Canceled).

24. (Canceled).

25. (Canceled).

26. (Canceled).

27. (Canceled).

28. (Canceled)

29. **(New)** A coin mechanism for a vending machine comprising:

a contoured channel configured to receive and direct at least one coin to a desired location in the channel, one coin of the at least one coins at least partially obstructing an opening formed in the channel surface; and

an actuator configured to be actuated by a user and to transmit a force onto said coin at least partially obstructing the opening to press the coin against the channel so as to pivotably displace the channel about an axis thereof to dispense a selected product from the vending machine.

30. **(New)** The coin mechanism of Claim 29, further comprising:

a product support member removably coupled to the channel member, the product support member configured to releasably support a selected product disposed in a product receptacle, the product support member configured to be displaced by the pivotal displacement of the channel member to dispense the selected product to the user, the

Appl. No. : 10/602,796
Filed : June 24, 2003

support member further configured to releasably support at least one product in the product receptacle disposed above the selected product during the dispensation of the selected product.